



Gas Detection Technology

Model PT395-H2S (MOS) Hydrogen Sulfide Sensor (3 Alarm Relay Contacts)

Features

- Microprocessor based modular design
- Solid State MOS Sensor Technology
- Industry standard 4-20mA output
- Field adjustable Low & High Alarm levels
- Single point Non-Intrusive calibration
- Bright 3 digit LED display
- Displays gas concentration in ppm, calibration prompts and sensor fault codes
- Suitable for use in Hazardous Location



Description

Model PT395-H2S is a microprocessor-based sensor designed to detect hydrogen sulfide in parts per million (ppm) level. The unit features easy one-man calibration initiated by simply activating a magnetic switch and applying the gas.

The complete sensor consists of a stainless steel sensor head assembly, a user connection board and a transmitter board assembly. All of the sensor electronics are enclosed in an explosion proof instrument box. Sensor modular design allows easy maintenance, troubleshooting and high reliability. Standard features also includes a linear 4-20mA signal output proportional to the full scale detection range and two (2) fully programmable alarm relays and a Fault relay.

The sensor transmitter board includes a three (3) digit LED display for continuous indication of the gas concentration. The calibration mode, alarm and fault status of the sensor are also indicated on the digital display. In the normal operating mode the digital display and 4-20mA reading is proportional to the gas concentration detected by the sensor. In the calibration mode the digital display indicates the calibration status, alarm relay outputs are inhibited and analog signal output is set to 2 mA to avoid any false alarm by the control monitor. In the sensor fault mode the transmitter drops the output signal to < 1 mA.



Model PT395 Stand Alone sensor for H₂S (MOS)

Specifications

Sensor Type

Metal Oxide Semiconductor (MOS)

Measuring Range

0 to 100 parts per million (ppm)

Repeatability

± 2 ppm of gas applied

Response Time

T50 < 20 seconds

T90 < 1 minute with 100% FS gas applied

Construction

Copper free cast aluminum junction box
316 Stainless Steel Detector head assembly

Classification

Class I, division 1, Groups B,C & D

Operating Temperature

-40°F to +158°F (-40°C to +70°C)

Operating Humidity

0% to 95% RH, non-condensing

Mechanical Specifications

Length: 7 inches (178 mm)

Width: 5 inches (127 mm)

Height: 4.5 inches (114 mm)

Display

Bright 3 digit LED display

Status Indicators

Three-digit display for gas concentration,
Alarm relay status, calibration mode and
sensor fault status.

Approvals

CSA / ATEX for use in Hazardous
Locations

CSA Standard C22.2 No 30-M1985 &
C22.2 No 142-M1987

Input Power

14-28 VDC. 24 VDC nominal

Power Consumption

Typical 180mA @ 24 VDC

Alarm Relays

3 Alarm Relays, Low, High and Fault
Fully programmable. 0 to Full scale
Range of the sensor, Latching or Non-
Latching

Relay Ratings

SPDT Form "C" type Relay contacts
0.5 Amp @ 125 VAC or
2 Amps @ 30 VDC

Analog Output

Linear 4-20mA (300 Ohms max. load)
2.0 mA - Calibration mode
< 1.0 mA - Sensor malfunction

Calibration

Non-Intrusive activated by internal
magnetic switch

Cable Requirement

3 wire shielded cable. Max loop
resistance of 20 Ohms @ 24 VDC
nominal

Cable Entry Hub

¾" NPT Female

Pem-Tech, Inc.

12144 Dairy Ashford, Bldg # 2 • Sugar Land, Texas 77478 • USA
Ph: 281-494-2079 Fax: 281-494-2167
www.pem-tech.com Email: sales@pem-tech.com