



ISO9001:2000  
Certified

## Gas Detection Technology

### **Ultra 1000** Combustible Gas Addressable Sensor

#### Features

- RS-485 MODBUS Serial Output
- 4-20mA Analog Output
- 12-28 VDC Operation
- Automated Non-Intrusive Calibration
- Fully Adjustable Alarm Relay
- Lower wiring costs



#### Description

Ultra 1000 series is a microprocessor based addressable sensor for detection of combustible gases. The self-contained sensor features user friendly interface and menu driven calibration procedure and configuration.

The complete sensor consists of a stainless steel sensor head assembly, a user connection board and a transmitter board assembly. All of the sensor electronics are enclosed in an explosion proof instrument box. The unit's modular design allows easy maintenance, troubleshooting and high reliability.

The unit provides a 4-20mA signal proportional to 0 to 100% of the detection range. In addition the sensor may be addressed via MODBUS RTU interface. The MODBUS output provides sensor status, alarm & fault conditions. Alarm levels can be programmed via MODBUS RTU or via magnetic switch on the face of the transmitter board assembly.

Ultra 1000 can be calibrated in less than 2 ½ minutes. The calibration and the set-up parameters are retained in a non-volatile memory.

## Ultra1000 Addressable Sensor for Combustible Hydrocarbons

### Specifications

#### Sensor Type

Continuous diffusion Catalytic Bead

#### Measuring Range

0 to 100 % LEL

#### Repeatability

± 2 % Full scale

#### Zero Drift

< 5% per year

#### Response Time

T50 < 10 seconds

T90 < 30 seconds

with 100% LEL methane gas applied

#### Classification

Class I, division 1, Groups B,C & D

#### Operating Temperature

-40°F to +158°F (-40°C to +70°C)

#### Operating Humidity

10% to 90% RH, non-condensing

#### Status Indicators

LC Display for gas concentration,  
Alarm relay status, calibration mode and  
sensor fault status.

#### Mechanical Specifications

Length: 7 inches (178 mm)

Width: 5 inches (127 mm)

Height: 4.5 inches (114 mm)

#### Display

2 lines by 8 Character LC Display with back light

#### Input Power

14-28 VDC. 24 VDC nominal

#### Power Consumption

150mA @ 24 VDC typical

#### Alarm Relays

Fully programmable. 0 to Full scale range  
of the sensor. Latching or Non-Latching.

#### Relay Ratings

SPDT Form "C" type Relay contacts  
5 Amps @ 250 VAC or 30 VDC

#### Analog Output

Linear 4-20mA (300 Ohms max. load)  
2.0 mA - Calibration mode  
< 1.0 mA - Sensor malfunction

#### Interface

RS-485 MODBUS RTU (2 wire)  
at 9600 Baud rate

#### Calibration

Non-Intrusive activated by internal  
magnetic switch

#### Cable Entry Hub

3/4" NPT Female

### **Pem-Tech, Inc.**

12144 Dairy Ashford, Bldg # 2 • Sugar Land, Texas 77478 • USA

Ph: 281-494-2079

Fax: 281-494-2167

www.pem-tech.com

Email: sales@pem-tech.com